

YHS Slide Valve



Product Features

- * Normally working with main valve together, not be used separately
- * Provide assistance to control the system better

How to Order?

Series No.	Port Size	Type	Thread Type
YHS: Slide valve	06: 1/8" 15: 1/2" 08: 1/4" 20: 3/4" 10: 3/8" 25: 1"	Blank: Standard type MM: Double male thread type FF: Double female thread type MF: One male and the other female type	Blank: G P: PT T: NPT

Order Example:


YHS slide valve, 1/4" port size, double male thread type, G thread, ERP code is: YHS-08MM

Specifications


Model	YHS-06	YHS-08	YHS-10	YHS-15	YHS-20	YHS-25
Working medium	Clean air(After 40 μ m filtration)					
Acting type	Manul direct acting					
Lubrication	Not required					
Working pressure (MPa)	0~1.0					
Guaranteed pressure (MPa)	1.5					
Working temperature (°C)	-5~60					
Port size	1/8"	1/4"	3/8"	1/2"	3/4"	1"

Main Dimension


Standard type




Double female thread type (FF)



One male and the other female thread type (MF)



Double male thread type (MM)



Model	A	B1	B2	B3	B4	C
YHS06	20	38	38	38	46	20
YHS08	32	58	58	58	68	26
YHS10	32	58	58	58	69	32
YHS15	40	80	80	80	94	38
YHS20	45	85	85	85	101	46
YHS25	45	85	85	85	101	52

Model	D	E1	E2	F1	F2
YHS06	14	G1/8"	G1/8"	G1/8"	G1/8"
YHS08	19	G1/4"	G1/4"	G1/4"	G1/4"
YHS10	22	G3/8"	G3/8"	G3/8"	G3/8"
YHS15	27	G1/2"	G1/2"	G1/2"	G1/2"
YHS20	34	G3/4"	G3/4"	G3/4"	G3/4"
YHS25	38	G1"	G1"	G1"	G1"